

Tub Open Top Container



A WASTEBUILT COMPANY

- Many options offer the versatility to handle most applications
- A variety of understructures for to fit most hoist models and manufactures
- Easy to load
- Economical
- Meets ANSI standards for safety



The Galfab Advantage



Vertical Lift Latch and Standard Hinge System

Secures the door in 3 places ensuring safe transport and easy unloading or the container and increased safety of the operator.



Nose Cone Roller

Fits most manufacturers hoists helping ensure smooth pick up and drop off of the container.



Greaseable Rear Roller

Rollers add to the longevity and durability of the container.

Standard Features

- 6 x 8 Greaseable Rear Ground Rollers
- Single Rear Door
- 6 x 2 x 1/4" Long Sills
- 3" Channel Cross Sills
- Cross Sills on 16" Centers
- Each Cross Sill Gussetted
- Solid Steel Nose Cone
- Structural Channel Rub Rails
- 64" Wide Floor

Options

- Standard, Medium, or Heavy Duty
- Gasketed Tailgate
- Front Rollers
- Inverted Angles on Top Cap
- Heavy Duty Top Cap
- Ground Roller Option
- Heavy Duty Long Sills

DISTRIBUTED BY:

Tub Open Top Container

Options

Duties	
Standard	7ga. Floor/10 ga. Sides
Medium	7ga. Floor/7 ga. Sides
Heavy	1/4 Floor/7 ga. Sides

Understructures
Outside Rail (OR)
Deadlift (HH)
Dempster Dino
Hook Lift
Dual Understructures
Misc. Other

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

Features



Front Ground Roller



A-Frame for Hooklift



Tarp Tie Down Hooks



Optional Patented Articulating Hinge for Gasketed Door

Models

Model	Inside Length	Inside Height	Rated Cubic Yards
TOT 1436	14'	36"	10
TOT 1454	14'	54"	15
TOT 1466	14'	66"	20
TOT 1648	16'	48"	15
TOT 1660	16'	60"	20
TOT 1842	18'	42"	15
TOT 1854	18'	54"	20
TOT 1866	18'	66"	25
TOT 2036	20'	36"	15
TOT 2048	20'	48"	20
TOT 2060	20'	60"	25
TOT 2242	22'	42"	20
TOT 2254	22'	54"	25
TOT 2266	22'	66"	30